SAFETY DATA SHEET

KURUMA POLY PUTTY



Rev.01/21

1. Identification of the substance/preparation and of the company/undertaking

Product name	:	KURUMA POLY PUTTY
Product type	:	Paint
Product use	:	Auto Refinish
Supplier/Manufacturer	:	TOA Performance Coating Corporation Co., Ltd.
Address	:	31/1 Moo 3, Debaratana Rd., KM.23, Bangsaothong,
	:	Amphur Bangsaothong, Samuthprakarn, 10540 Thailand.
Tel.	:	+66(0)2335-5555
Fax.	:	+66(0)2312-8928
Emergenycy telephone number	:	+66(0)235-5555 #1999

2. Hazards identification

Classification of the substance or mixture

Flammable liquid and vapour	Category 3
Skin corrosion / Irritation	Category 2
Serious eyes damage / Eyes irritation	Category 2
Specific target organ systemic toxicity-Single exposure	Category 3
Specific target organ systemic toxicity-Repeated exposure	Category 1
Aspiration Hazard	Category 1
Acute aquatic hazard	Category 2
Long-term aquatic hazard	Category 3

GHS -Labelling

Pictogram symbols



Signal word	: Danger
Hazard statement	 H226 Flammable liquid and vapour H304 - May be fatal if swallowed and enters airways
	H315 - Causes skin irritation
	H320 - Causes eye irritation
	H335 May cause respiratory irritation
	H336 May cause drowsiness or dizziness
	H372 - Causes damage to organs through prolonged or repeated exposure
	H401 - Toxic to aquatic life
	H412 - Harmful to aquatic life with long lasting effects
Precautionary statement	2 Prevention
Precautionary statement	 Prevention P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking.
Precautionary statement	
Precautionary statement	P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking.
Precautionary statement	P210 - Keep away from heat/sparks/open flames/hot surfaces.– No smoking. P233 - Keep container tightly closed.
Precautionary statement	P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment
Precautionary statement	 P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/lighting
Precautionary statement	 P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/lighting P242 - Use only non-sparking tools.
Precautionary statement	 P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/lighting P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge.
Precautionary statement	 P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/lighting P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
Precautionary statement	 P210 - Keep away from heat/sparks/open flames/hot surfaces No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/lighting P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathingdust/fume/gas/mist/vapours/spray.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection/face protection

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 F ON SKIN: Wash with plenty of soap and water

P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off

P304 + P340 IF INHALED: Remove victim to fresh air andkeep at rest in a position comfortable forbreathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician ifyou feel unwell.

P314 - Get medical advice/attention if you feel

P321 - Specific treatment

P331 - Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use appropriate media for extinction.

Storage

P403 + P233 Store in a well-ventilated place. Keep containertightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

Disposal

P501 - Dispose of contents/container to appropriate waste site or reclaimer in accordance with local/ regional / nation or national regulations.

3. Composition/information on ingredients

Chemical name	CAS No.	Concentration(%)
Polyester resin	Not Assigned	20 - 30
Styrene monomer	100-42-5	1 - 10
Titanium dioxide or Colouring Pigments	13463-67-7	1 - 10
Extender Pigments	-	60 - 65
Colouring Pigments	-	<0.2

4. First aid measures.

General Advice Eye Contact	:	If symptoms persist, call a physiciam. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minute. Get medical advice / attention.
Skin Contact	:	Do NOT use solvents or thinner .Remove contaminated clothing immediately and
		Wash off with plenty of water .If skin irritation persists, get medical advice / attention.
Inhalation	:	Move to fresh air. Get medical attention if symptoms occur. Risk of serious damage to the lungs.
Ingestion	:	Rinse mouth with fresh water . Do not induce vomiting. Call a physician immediately. If vomiting occurs naturally, have victim lean forward.

5. Fire-fighting measures

Extinguishing Media		
Suitable extinguishing media	:	Use water spray, dry chemical powder, Carbon dioxides, foam
Unsuitable extinguishing media	:	Do not use water jet
Special hazards arising from the s	ubst	ance or mixture
Fire hazard	:	In a fire or if heated, a pressure in crease will occur and the container may burst, with the risk of a subsequent explosion. Fire water contaminated with this material must be contained and

prevented from being discharged to any waterway, sewer or drain.

Thermal decomposition products	:	Decomposition products may be hazardous to health.
Special protective equipment and precautions for fire-fighters		
Protective actions for firefighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a
		fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done with out risk. Use water spray to keep fire-exposed containers cool.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

• • •	•••	
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch
		or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in
		hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate
		respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	Do not attempt to take action without suitable protective equipment
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
		Inform the relevant authorities if the product has caused enviromental pollution. Water polluting
		material. May be harmful to the environment. If released in large quantities.
Methods and material for contai	nment	and cleaning up
	:	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

7. Handling and storage

Handling	Handle in good ventilated area.	
	Wash thoroughly hand and face after handling.	
	Close tightly container with closer necessarily during and after use.	
	Wear antistatic suits and shoes, while working.	
	Use handtool of spark proof type and ground equipment.	
	Wear proper protectors to avoid contact of skin or eyes when handling	
	open containers.	
	Install proper local ventilator and wear proper protector in closed space.	
Storage	Keep container closed and avoid direct sunlight.	
	Store in good ventilation.	
	Store with keeping away from ignition or heat source.	

8. Exposure controls/personal protection

Controlparameters	: Styrene monomer OSHA : PEL TWA 100 ppm NIOSH : REL TWA 50 ppm (215 mg/m3) REL STEL 100 ppm (425 mg/m3)
Engineeringcontrols	: Use only in a well-ventilated area. Use local exhaust ventilation
Personalprotection	
Respirationprotection	: Organic vapor respirator
Eye/Faceprotection	: Safety google and face shield
Skinprotection	: Wear protective clothing
Bodyprotection	: Wear protective clothing
Work/HygienicPractices	: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

9. Physical and chemical properties

Appearance and Colour

: Paste, Yellow

Odour	:	Solvent Odour
Odour Threshold	:	Not available
рН	:	Not available
Melting point/freezing point	:	Not available
Initial boiling point and boiling	:	Not available
Flash point	:	31 ⁰ C
Evaporation rate	:	Not available
Flammability (solid, gas)	:	Not available
Vapour pressure	:	Not available
Vapour density	:	Not available
Relative density at 25C	:	Not available
Solubility	:	None or poor in water
Log Pow	:	Not available
Auto ignition temperature	:	Not available
Decomposition temperature	:	Not available
Viscosity	:	Not available

10. Stability and reactivity

Reactivity	:	Not available
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous reactions will not occur under normal conditions.
Conditions to Avoid	:	High temperature, direct sunlight.
Materials to Avoid	:	Acid, alkaline and Strong oxidising agent and reducing agents or peroxide fumes.
Hazardous Decomposition	:	Carbon monoxide, Carbon dixide toxic or asphyxiating gases

11. Toxicological information

Acute oral toxicity	:	ATE mix (oral/rat) 35134 mg/kg (Not classified)
Acute dermal toxicity	:	ATE mix (skin/rabbit) 14053 mg/kg (Not classified)
Acute inhalation toxicity	:	ATE mix (inhale/rat) 82.92 mg/L/4 hr (Not classified)
Skin corrosion / irritation	:	Causes skin irritation
Serious eye damage/eye irritation	:	Causes eye irritation
Respiratory sensitization	:	Not classified
Skin sensitization	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT - single exposure	:	May cause respiratory irritation; or May cause drowsiness or dizziness
STOT - repeated exposure	:	Causes damage to organs
Aspiration hazard	:	May be fatal if swallowed and enters airways

12. Ecological information

Acute aquatic hazard Long-term aquatic hazard Persistence and degradability Bioaccumulative potential Mobility in soi Other adverse effects	::	Toxic to aquatic life Harmful to aquatic life with long lasting effects Not rapidly degradability Not available Not available Not available
Other adverse effects	:	Not available

13. Disposal considerations

Disposal methods	:	Dispose of contents in accordance with local/national and international regulations
		or handled by authorized waste collector in your country
Container Management	:	Dispose of container in accordance with all local, regional, national

14. Transport information

UN.Number	:	1263
ProperShippingName	:	Paint
UN.Class	:	3
PackingGroup	:	III
Environmentalhazards	:	NO
LandTransportation	:	Accord to each transportation under " ADR/RID code "
AirTransportation	:	Accord to each transportation under " ICAO/IATA code "
MaritimeTransportation	:	Accord to each transportation under " IMO/IMDG code "

15. Regulatory information

Thai regulation

 Thai land Notification of Ministry of Industry Subject. List of hazardous substances B.E. 2556 (2013)
 Thai land Notification of Ministry of Labour Subject.

List of hazardous chemicals B.E. 2556 (2013)

16. Other information of the second s	ation	
Created	:	April, 2021
References	:	
	1)	https://pubchem.ncbi.nlm.nih.gov/
	2)	https://www.nite.go.jp/chem/english/ghs/all_fy_e.html
	3)	United Stated National Library of Medicine: ChemIDplus Lite (ID PLUS)
		http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?CHEM
	4)	New Jersey Department of Health (DOH)
		http://web.doh.state.nj.us/rtkhsfs/qrsearch.aspx.
	5)	International Uniform ChemicaL Information Database (IUCLID)
		http://ecb.jrc.ec.europa.eu/esis/index.php?PGM=dat
	6)	CHEMTRACK
		http://www.chemtrack.org/Chem-Result.asp
	7)	SIGMA-ALDISH
		http://www.sigmaaldrich.com/MSDS/MSDS/DisplayMSDSPage.do?
		Occupational Safety & Health Administration (OSHA)
		http://www.osha.gov/dts/chemicalsampling/toc/chmcas.html

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.