SAFETY DATA SHEET

MATRIX THINNER #AX20



1. Identification of the substance/preparation and of the company/undertaking

Product name : MATRIX THINNER #AX20

Product type : Thinner
Product use : Auto Refinish

Supplier/Manufacturer : TOA Performance Coating Corporation Co., Ltd.

Address : 31/1 Moo 3, Debaratana Rd., KM.23, Bangsaothong,

Amphur Bangsaothong, Samuthprakarn, 10540 Thailand.

Tel. : +66(0)2335-5555

Fax. : +66(0)2312-8928

Emergenycy telephone number : +66(0)235-5555 #1999

2. Hazards identification

Classification of the substance or mixture

Category 2 Flammable liquid and vapour Acute inhalation toxicity Category 4 Skin corrosion / Irritation Category 2 Serious eyes damage / Eyes irritation Category 2 Reproductive toxicity Category 1B Specific target organ systemic toxicity-Single exposure Category 1 Specific target organ systemic toxicity-Repeated exposure Category 1 Aspiration Hazard Category 1 Acute aquatic hazard Category 2 Long-term aquatic hazard Category 2

GHS -Labelling

Pictogram symbols









Signal word : Danger

Hazard statement : H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation H320 - Causes eye irritation H332 Harmful if inhaled

H360 - May damage fertility or the unborn child

H370 - Causes damage to organs

H372 - Causes damage to organs through prolonged or repeated exposure

H401 - Toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Precautionary statement : Prevention

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat/sparks/open flames/hot surfaces.— No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/lighting

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P261 - Avoid breathing dust/fume/gas/mist/ vapours/spray.

P264 – Wash hand, mouth, etc. thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilatedarea.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection/face protection

P281 - Use personal protective equipment as required.

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 F ON SKIN: Wash with plenty of soap and water P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off

P304 + P340IF INHALED: Remove victim to freshair and keep at rest in a positioncomfortable

for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P307 + P311IF exposed: Call a POISON CENTER ordoctor/physician.

P314 - Get medical advice/attention if you feel

P321 - Specific treatment

P331 - Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use appropriate media for extinction.

P391 Collect spillage.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

Disposal

P501 - Dispose of contents/container to appropriate waste site or reclaimer in accordance with local/regional / nation or national regulations.

3. Composition/information on ingredients

Chemical name	CAS No.	Concentration(%)
Xylene	1330-20-7	45 - 50
Butyl acetate	123-86-4	15 - 20
Ethyl acetate	141-78-6	10 - 15
Ethylethoxypropyonate	763-69-9	5 - 10
PM Acetate	108-65-6	10 - 15

4. First aid measures.

General Advice : If symptoms persist, call a physiciam.

Eye Contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minute.

Get medical advice / attention.

Skin Contact : Do NOT use solvents or thinner .Remove contaminated clothing immediately and

Wash off with plenty of water .If skin irritation persists, get medical advice / attention.

Inhalation : Move to fresh air. Get medical attention if symptoms occur. Risk of serious damage

to the lungs.

Ingestion : Rinse mouth with fresh water . Do not induce vomiting. Call a physician immediately.

If vomiting occurs naturally, have victim lean forward.

5. Fire-fighting measures

Suitable extinguishing media : Use water spray, dry chemical powder, Carbon dioxides, foam

Unsuitable extinguishing media : Do not use water jet

Special hazards arising from the substance or mixture

Fire hazard : In a fire or if heated, a pressure in crease will occur and the container may burst, with the risk

of a subsequent explosion. Fire water contaminated with this material must be contained and

prevented from being discharged to any waterway, sewer or drain.

Thermal decomposition products : Decomposition products may be hazardous to health.

Special protective equipment and precautions for fire-fighters

Protective actions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a

fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done with out risk. Use water spray to keep fire-exposed

containers cool.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate

surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : Do not attempt to take action without suitable protective equipment

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Inform the relevant authorities if the product has caused environmental pollution. Water polluting

material. May be harmful to the environment. If released in large quantities.

Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

7. Handling and storage

Handling : Handle in good ventilated area.

: Wash thoroughly hand and face after handling.

Close tightly container with closer necessarily during and after use.

: Wear antistatic suits and shoes, while working.

Use handtool of spark proof type and ground equipment.

: Wear proper protectors to avoid contact of skin or eyes when handling

open containers.

Install proper local ventilator and wear proper protector in closed space.

Storage : Keep container closed and avoid direct sunlight.

Store in good ventilation.

: Store with keeping away from ignition or heat source.

8. Exposure controls/personal protection

Controlparameters : Xylene

OSHA: PEL-TWA 100 ppm (435 mg/m3)
PEL-STEL 150 ppm (655 mg/m3)
NIOSH: REL-TWA 100 ppm (435 mg/m3)

REL-STEL 150 ppm (655 mg/m3)

Butyl acetate

OSHA: PEL TWA 150 ppm (710 mg/m3)
PEL STEL 200 ppm (950 mg/m3)
NIOSH: REL TWA 150 ppm (710 mg/m3)

REL STEL 200 ppm (950 mg/m3)

PMI acetate

OSHA: CAPEL TWA 100 ppm (541 mg/m3) CAPEL STEL 150 ppm (811 mg/m3)

Ethyl Acetate

OSHA: PEL-TWA 400 ppm (1400 mg/m3) NIOSH: REL-TWA 400 ppm (1400 mg/m3)

Engineeringcontrols : Use only in a well-ventilated area. Use local exhaust ventilation

Personalprotection

Respirationprotection : Organic vapor respirator

Eye/Faceprotection : Safety google and face shield

Skinprotection : Wear protective clothing

Bodyprotection : Wear protective clothing

Work/HygienicPractices : Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

9. Physical and chemical properties

Appearance and Colour Liquid, Clear Odour Solvent Odour Not available Odour Threshold рН Not available Not available Melting point/freezing point initial polling point and polling Not available range Flash point 31 °C Evaporation rate Not available

Flammability (solid, gas)

Vapour pressure

Vapour density

Relative density at 25C

Solubility

Flammability (solid, gas)

Not available

Log Pow : Not available
Auto ignition temperature : Not available
Decomposition temperature : Not available
Viscosity : Not available

10. Stability and reactivity

Reactivity : Not available

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous reactions will not occur under normal conditions.

Conditions to Avoid : High temperature, direct sunlight.

Materials to Avoid : Acid, alkaline and Strong oxidising agent and reducing agents or peroxide fumes.

Hazardous Decomposition : Carbon monoxide , Carbon dixide toxic or asphyxiating gases

11. Toxicological information

Acute oral toxicity : ATE mix (oral/rat) 5755 mg/kg (Not classified)

Acute dermal toxicity : ATE mix (skin/rabbit) 10634 mg/kg (Not classified)

Acute inhalation toxicity : ATE mix (inhale/rat) 4.30 mg/L/4 hr (Category 4)

Skin corrosion / irritation : Causes skin irritation
Serious eye damage/eye irritation : Causes eye irritation

Respiratory sensitization : Not classified
Skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child

STOT - single exposure : Causes damage to organs STOT - repeated exposure : Causes damage to organs

Aspiration hazard : May be fatal if swallowed and enters airways

12. Ecological information

Acute aquatic hazard : Toxic to aquatic life

Long-term aquatic hazard : Toxic to aquatic life with long lasting effects

Persistence and degradability : Not rapidly degradability

Bioaccumulative potential : Not available

Mobility in soi : Not available

Other adverse effects : Not available

13. Disposal considerations

Disposal methods : Dispose of contents in accordance with local/national and international regulations

or handled by authorized waste collector in your country

Container Management : Dispose of container in accordance with all local, regional, national

and international regulations.

14. Transport information

UN.Number : 1263
ProperShippingName : PAINT

UN.Class : 3
PackingGroup : III
Environmentalhazards : NO

LandTransportation : Accord to each transportation under " ADR/RID code "

AirTransportation : Accord to each transportation under " ICAO/IATA code "

MaritimeTransportation : Accord to each transportation under " IMO/IMDG code "

15. Regulatory information

Thai regulation : Thai land Notification of Ministry of Industry Subject.

List of hazardous substances B.E. 2556 (2013)

Thai land Notification of Ministry of Labour Subject.
List of hazardous chemicals B.E. 2556 (2013)

16. Other information

Created : April, 2021

References

1) https://pubchem.ncbi.nlm.nih.gov/

2) https://www.nite.go.jp/chem/english/ghs/all_fy_e.html

3) United Stated National Library of Medicine: ChemIDplus Lite (ID PLUS)

http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?CHEM

4) New Jersey Department of Health (DOH)

http://web.doh.state.nj.us/rtkhsfs/qrsearch.aspx.

5) International Uniform ChemicaL Information Database (IUCLID)

http://ecb.jrc.ec.europa.eu/esis/index.php?PGM=dat

6) CHEMTRACK

http://www.chemtrack.org/Chem-Result.asp

7) SIGMA-ALDISH

http://www.sigmaaldrich.com/MSDS/MSDS/DisplayMSDSPage.do?

Occupational Safety & Health Administration (OSHA)

http://www.osha.gov/dts/chemicalsampling/toc/chmcas.html

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.