

# **CAPTAIN Putty Sander PACS**

# **Product Description**

Name : PACS
Type : Dry Sanding
Backing : Awt- Latex Paper
Bonding : Resin over Resin
Grain : Aluminium Oxide
Coating : Open Coat
Shape : Roll , Sheet









#### **Product Features**

- High performance sanding ability for wall putty surface
- · Long lasting sanding ability
- No clogging

## **Applications**

#### <u>Workpieces</u>

- Wood
- Furniture
- Wall putty

#### Available Sander / Grinder

- Hand Sanding
- Orbital Sander

### Recommendations

• Select grit number of abrasive paper suitable to the sanding surface

Appliacation	Grit No.
Cutting down Wood surface	#120
Surface Condition	#150-#180
Wall putty	#120-#180

# Packaging Size

Grit no.	Sheet/ Sleeve	Sleeve/ Carton	Sheet/ Carton
120-180	50	10	500

# **Handling and Storage**

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

# **Safety and Disposal**

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment



TOA PERFORMANCE COATING CORPORATION CO., LTD. 31/1 Moo. 3. Debaratana Road., Bangsaothong, Amphur Bangsaothong, Samutprakarn 10570 Thailand Tel. +66-2335-5555 Fax. +66-2312-8929

บริษัท ทีโอเอ เพอฟอร์มานซ์ โค๊ทติ้ง คอร์ปอเรชั่น จำกัด 31/1 หมู่ 3 ถ.เทพรัตน ต.บางเสาธง อ.บางเสาธง จ.สมุทรปราการ 10570 โทร. 0-2335-5555 โทรสาร 0-2312-8920

First Issue Date: 20/11/2021 Last update: 4/1/2022

Revision No.: 1