

DSCS-TOA

Product Description

- Name : DSCS
- Type : Dry Sanding
- Backing : Cwt-Oil Paper
- Bonding : Resin over Resin
- Grain : Silicon Carbide
- Coating : Semi Open Coat
- Shape : Sheet



Available Grit													
100	120	150	180	220	240	280	320	360	400	500	600	800	1000
■	■	■	■	■	■	■	■	■	■	■	■	■	■

Product Features

- High performance cutting and sanding ability.
- Excellent grain support.
- Provide high stock removal.
- Excellent anti-clogging from sanding dust.
- Long lasting sanding ability.

Applications

- Workpieces
 - Wood and Furniture
 - Wooden Paint
 - Lacquer sanding sealer
 - Plastic
- Available Sander / Grinder
 - Hand Sanding
 - Orbital Sander

Recommendations

- Select grit number of abrasive paper suitable to the sanding surface

Application	Grit No.
• Cutting down Wood surface	100-150
• Surface Condition	180-240
• Primer, Sealer	280-320
• Topcoat, Clear Laquer	360-600
• Finishing	800-1000

Packaging Size

Grit no.	Sheet/ Sleeve	Sleeve/ Carton	Sheet/ Carton
100-240	60	10	600
280-1000	60	20	1200

Handling and Storage

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

Safety and Disposal

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment