

TOA Putty Sander WACS

Product Description

Name : WACS
 Type : Dry Sanding
 Backing : Cwt- Kraft Paper
 Bonding : Resin over Resin
 Grain : Aluminium Oxide
 Coating : Open Coat
 Shape : Roll , Sheet

Available Grit						
60	80	100	120	150	180	220
▪	▪	▪	▪	▪	▪	▪



Product Features

- High performance sanding ability for wall putty surface
- Long lasting sanding ability
- No clogging

Applications

- Workpieces
- Wood
 - Furniture
 - Wall putty
- Available Sander / Grinder
- Hand Sanding
 - Orbital Sander

Recommendations

- Select grit number of abrasive paper suitable to the sanding surface

Application	Grit No.
• Cutting down Wood surface	#60-#120
• Surface Condition	#150-#220
• Wall putty	#60-#220

Packaging Size

Grit no.	Sheet/ Sleeve	Sleeve/ Carton	Sheet/ Carton
60-150	50	10	500
180-220	50	20	1000

Handling and Storage

- Avoid dampish places
- Avoid direct exposure to sunlight
- Avoid close to the source of heat

Safety and Disposal

- For full Health and Safety information please refer to Material Safety Data Sheet
- Observe the precautionary notices displayed on the sleeve
- Goggles and suitable protective equipment must be worn while using these products
- Good ventilation must be provided in the working environment