

Automotive Refinish Technical Data Sheet

Rev.01/21

Product Description

Kuruma Clear 4:1 K4050 Fast Dry 1.5Hr. is two-pack acrylic polyurethane topcoat.

It is designed for for spot and panel application over Kuruma base coat. It is a high gloss and good retention, easy spraying and fast drying, excellent film durability and weather resistance

Substrate preparation

To secure lasting adhesion to the subsequent product all surfaces shall be clean, dry and free from any contamination.

Mixing Ratio

- Two Component System

KURUMA CLEAR 4:1 K4050 FAST DRY 1.5Hr.

	weignt	volume
KURUMA CLEAR 4:1 K4050 FAST DRY 1.5Hr. Part A	100	100
KURUMA CLEAR 4:1 K4050 FAST DRY 1.5Hr. Part B	25	25
Thinner	0-10	0-10

Mix Part A and Part B, strictly follow mix ratio recommendations before and stir for 2-3 minutes until the mixture is homogeneous before application.

- Pot life 2 hour after mixing Base with hardener @30°C

Thinner

Kuruma Standard Thinner No.20 or Butyl Acetate

Viscosity For Spray

	Viscosity (sec) @30°C
Ford Cup No.4	13.5 - 15.5

Gravity Feed

Set-up

Full pattern Flow - 2.5 turns from fully closed set-up

Nozzle size

Spray gun

1.2 - 1.8 mm. (Please refer to spray gun manufacturer)

Spray pressure

1.2 - 1.5 Bar

Number of spray coats

Recommended apply 2 coats

- Light to medium first coat
- Full wet second coat
- Wet film thickness (per coat) 30 to 35 Microns
- Dry film thickness (per coat) 20 to 25 Microns

Flash-off time

Between coat: 2 - 3 mins

Drying time

Drying time	Air dry (30 °C)
Surface dry	8 - 10 mins
Polishing time	1.5 - 2 hrs
Full cure	7 days

Handling and Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.

Shelf life

- 48 months at <40 °C
- The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Safety and Disposal

- Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.
- For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Safety Data Sheet.