



KURUMA POLY PUTTY

Rev.1/21

Product Description

KURUMA POLY PUTTY is poly putty or air dry putty which is quick dry, very good sandability and non-sinking. It's suitable for thin application and easy to be smooth putty knife because it's fine particle. It doesn't stick with sandpaper and good featheredge. It's very strong internal adhesion sinking under right mixing ratio between base and hardener.

Substrate preparation

- Remove the old paint film with dry sandpaper no.60 and 80 on sanding sequence, then make featheredge with sandpaper no. 120, 180 and 240 on sanding sequence.
- Clean surface to be dry and without wax, grease, dust and foreign matters.

Mixing Ratio

- Two Component System

	Weight
KURUMA POLY PUTTY Part A	100
KURUMA POLY PUTTY Part B	2

- Mix Part A and Part B, strictly follow mix ratio until the mixture is homogeneous before application.
- After mixed, apply within 5-10 minutes

Usage

- Applied by putty knife to increase gradually film thickness until full level.
- Dry to sand for 30 mins.
- Sand with dry sandpaper no. 120, 180 and 240 on sanding sequence or wet sandpaper no. 180, 240 and 320 on sanding sequence.

Handling and Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Shelf life

- Keep at low temperature area and should use within 6 months after manufactured.

Safety and Disposal

- Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.
- For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Safety Data Sheet.