

MATRIX CLEAR	2:1 HI-GLOSS Rev.1/2
Product Description	MATRIX CLEAR 2:1 HI-GLOSS is two-pack acrylic polyurethane topcoat with excellent gloss retention. It is designed for exterior. It has excellent durability, good adhesion, and excellent chemical resistance. It is a high gloss. Can be applied on NC lacquer, acrylic lacquer and 2K urethane paint.
Substrate preparation	To secure lasting adhesion to the subsequent product all surfaces shall be clean, dry and free from any contamination.
Mixing Ratio	- Two Component System
	Weight Volume MATRIX CLEAR 2:1 HI-GLOSS Part A 100 100 MATRIX CLEAR 2:1 HI-GLOSS Part B 50 50 Thinner 0-10 0-10 Mix Part A and Part B, strictly follow mix ratio recommendations before and stir for 2-3 minutes until the mixture is homogeneous before application. - Pot life 3 hour after mixing Base with hardener @ 30° C
Thinner	Kuruma Standard Thinner No.20
Viscosity For Spray	Viscosity (sec) @30°C Ford Cup No.4 15 - 17
Spray gun Set-up Nozzle size Spray pressure	Gravity Feed Full pattern Flow - 2.5 turns from fully closed set-up 1.2 - 1.5 mm. (Please refer to spray gun manufacturer) 1.2 - 1.5 Bar
Number of spray coats	Recommended apply 2 coats - Light to medium first coat - Full wet second coat - Wet film thickness (per coat) 50 to 60 Microns - Dry film thickness (per coat) 30 to 35 Microns
Flash-off time	Between coat : 3 - 5 mins
Drying time	Drying timeAir dry (30 °C)Surface dry25 - 30 minsPolishing time>6 hrsFull cure7 days
Handling and Storage	The product must be stored in accordance with national regulations. Storage conditions are to keep the
Shelf life	 containers in a dry, cool, well ventilated space and away from source of heat and ignition. 48 months at <40 °C The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.
Safety and Disposal	 Please observe the precautionary notices displayed on the container. Use under well ventilated conditions Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately. For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Safety Data Sheet.