

MATRIX CLEAR 2:1 M2070 EXTRA SOLID

Product Description	MATRIX CLEAR 2:1 M2070 EXTRA SOLID is two-pack acrylic polyurethane topcoat with good gloss retention. It is designed for exterior. It has excellent durability, good adhesion, and excellent chemical resistance.				
	It is a high gloss. Can be applied on NC lacquer, acrylic lacquer and 2K urethane paint.				
Substrate preparation	To secure lasting adhesion to the subsequent product all surfaces shall be clean, dry and free from any contamination.				
Mixing Ratio	- Two Component System				
			Weight	Volume	
	MATRIX CLEAR 2:1 M207	70 EXTRA SOLID Part A	100	100	
	MATRIX CLEAR 2:1 M2070 EXTRA SOLID Part B		50	50	
	Thinner 0		0-10	0-10	
	Mix Part A and Part B, strictly follow mix ratio recommendations before and stir for 2-3 minutes until the				
	mixture is homogeneous before application.				
	- Pot life 1.5 hour after n	nixing Base with harden	er @30ºC		
Thinner	Kuruma Standard Thinner No.20				
Viscosity For Spray	Viscosity (sec) @30°		@30°C]	
	Ford Cup No.4	15 - 17			
				_	
Spray gun	Gravity Feed				
Set-up	Full pattern Flow - 2.5 turns from fully closed set-up				
Nozzle size	1.2 - 1.5 mm. (Please refer to spray gun manufacturer)				
Spray pressure	1.2 - 1.5 Bar				
Number of spray coats	- Light to medium first coat - Full wet second coat				
	- Wet film thickness (per coat) 50 to 60 Microns				
	- Dry film thickness (per coat) 30 to 35 Microns				
Flash-off time	Between coat : 3 - 5 mins				
Drying time	Drying time	Air dry (30 °C)]		
	Surface dry	20 - 30 mins	_		
	Polishing time	4 - 5 hrs	-		
	Full cure	7 days]		
Handling and Storage	The product must be stored in accordance with national regulations. Storage conditions are to keep the				
········					
Shelf life	containers in a dry, cool, well ventilated space and away from source of heat and ignition. - 48 months at <40 0 C				
Sheh hie					
	- The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers				
	must be kept tightly close	ed.			
Safety and Disposal	- Please observe the pred	cautionary notices displa	ved on the	container. Use under well ventilated condition	ons.
	 Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought 				
	immediately.				
	- For detailed information on the health and safety hazards and precautions for use of this product, we				
	refer to the Safety Data Sheet.				